

# VT07-B26L-W

## Smart Video Indoor Monitor



The VT07-B26L-W is a smart video indoor monitor provides multiple functions, including two-way talking video intercom, emergency call, and security alarm, etc. It also supports communication via SIP 2.0 protocol with IP phone and IP-PBX solution. It allows constructor to make an easy configuration and installation.

### Features

- 2-way audio and video communication over IP network
- 7-inch capacitive touch screen (1024 x 600)
- Powered by PoE (IEEE 802.3af) or power adapter (DC12V/2A)
- Support Wi-Fi (IEEE 802.11 b/g/n/ac) connection
- Support up to 8 IPC channels display
- Support TF card (max. 32GB)

## Specifications

Physical	
System	Linux
RAM	128 MB
ROM	128 MB
Front Panel	Plastic
Power Supply	PoE (802.3af) or DC 12V/2A
Standby Power	2 W
Rated Power	9 W
Ethernet Port	2 x RJ45, 10/ 100 Mbps self-adaptive
Wi-Fi	IEEE 802.11 b/ g/ n, @ 2.4 GHz
TF Card Slot	1 (max. 32GB)
RS485	1
Power Output	1 (12V/100mA)
Doorbell Input	Max. 8 input
Alarm Input	Support 8 sensor zones: smoke, gas, PIR, door, window, panic and flood
Installation	Wall mount (on flat surface)
Dimension	195 x 130 x 14.5 mm
Working Temperature	-10°C to +55°C

Storage Temperature	-40°C to +70°C
Working Humidity	10% to 90% (non-condensing)
Display	
Display	7-inch TFT LCD
Screen	Capacitive touch screen
Resolution	1024 x 600
Audio	
Audio Codec	G.711
Echo Cancellation	support
DTMF	RFC2833
Microphone	Built-in microphone
Speaker	8Ω / 1W
Video	
Video Codec	H.264
Networking	
Protocol	SIP 2.0, UDP, TCP, RTP, RTSP, NTP, DNS, HTTP, DHCP, IPV4, ARP, ICMP

# Configuration

